

Item No. 1012CP INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

- 1. Thread mounting nipple (6) into the single mounting bar (2) and secure it with the hex nut (5).
- 2. Secure the single mounting bar(2) with box screws (3) to the outlet box(1).
- 3. Pull out the outlet wire and ground wire from the outlet box(1). Make wire connections
- --Connect white wire from light to White wire from power source with wire nut(4).
- --Connect Black from light to Black wire from power source with wire nut(4).
- --Loop the ground wire to single mounting bar(2) with a green screw(7).
- 4. After wires are connected, tuck them carefully inside outlet box, then, attach the fixture (8) against the outlet box(1), allowing for the mounting nipple (6) to protrude through the hole of the frame backplate, then, secure with the ball nut(10).
- 5 In stall halfs into the so-shot
- 5. Install bulbs into the socket.
- 6. Close the door, insert the latch (9)

Please do not exceed the Maximum capacity recommended on the socket INSTALLATION IS NOW COMPLETED

