

Allatoona Business Center

180 Joe Frank Harris Pkwy SE, Building 500, Suite 550, Cartersville, GA 30120

Phone: (866) 845-5451 • Fax: (866) 816-6165

E: service@acclaim-lighting.com • W: www.acclaim-lighting.com

Item No. 1030 BK INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90° C supply conductors.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

- 1. Turn off the power at fuse or circuit breaker.
- 2. Secure the mounting plate (3) to the outlet box (1) using box screws (4).
- 3. Electrical Connections:
 - Connect ground wire (2) from supply source to fixture ground wire using wire connector (6)
 - Connect white wire (5) from light to white wire from power source using wire connector (6).
 - Connect black wire (7) from light to black wire from power source using wire connector (6).
- 4. Attach the fixture (10) to the mounting plate (3) by inserting the screw, then secure with the knob (9) and waterproof washer (8).
- 5. Install the bulb (not included). Do not exceed the recommended wattage located on the fixture body.

NOTE: After securing fixture to the wall it is recommended that the gap between the wall and the fixture back plane be sealed on the top and both sides, with a good quality waterproof caulk or silicone sealant (NOT INCLUDED).

